

HIGHLIGHTS

TOUGH	<ul style="list-style-type: none"> • Heavy-duty Rotax® engine • Smooth, durable and responsive transmission • True Can-Am DNA with a strong identity
CAPABLE	<ul style="list-style-type: none"> • Work or ride with confidence • Meaningful and versatile functionality • Easy handling and capabilities
CLEVER	<ul style="list-style-type: none"> • Advanced comfort and intuitive cockpit with optimized visibility • Multifunction cargo box with sturdy tailgate and smart storage • 1 year maintenance-free and easy access to key maintenance components



ENGINE	HD7	HD9	HD10
Type	52 hp / 41 lb-ft, Rotax® ACE (Advanced Combustion Efficiency) 650 cc single cylinder, liquid-cooled	65 hp / 59 lb-ft, Rotax® 976 cc, V-twin, liquid-cooled	82 hp / 69 lb-ft, Rotax® 976 cc, V-twin, liquid-cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)		
Transmission	PDrive primary CVT with engine braking and Electronic Drive Belt Protection L/H/N/R/P	PRO-TORQ CVT Transmission with Quick Response System (QRS), high-airflow ventilation and Electronic Drive Belt Protection Extra L/H/N/R/P	
Drive Train	Selectable Turf Mode /2WD/4WD with Visco-Lok¹ QE auto-locking front differential	Selectable Turf Mode/2WD/4WD with Visco-Lok¹ QE auto-locking front differential Open front differential with ABS system	
Driving Assistance	Electronic Hill Descent Control ECO™/ECO™ Off/Work modes		
Power Steering	Dynamic Power Steering (DPS)		

SUSPENSIONS

Front Suspension	Double A-arm/10 in. (25.4 cm) travel	Arched double A-arm/11 in. (27.9 cm) travel
Front Shocks	Twin tube gas-charged shocks	
Rear Suspension	TTA with external sway bar/10 in. (25.4 cm) travel	Arched TTA with external sway bar/11 in. (27.9 cm) travel
Rear Shocks	Twin tube gas-charged shocks	

TIRES & WHEELS

Front Tires	Maxxis Coronado 2.0 27 x 9 x 14 in.
Rear Tires	Maxxis Coronado 2.0 27 x 11 x 14 in.
Wheels	14 in. cast-aluminum

BRAKES

Front	Dual 220 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 220 mm disc brakes with hydraulic twin-piston calipers
	Brake-holding mechanism

DIMENSIONS & CAPACITIES

	HD7	HD9	HD10
Cage	Profiled cage, ROPS approved		
Estimated Dry Weight	1,516 lb (687.8 kg)	1,572 lb (713 kg)	1,594 lb (723 kg)
L x W x H	121 x 62 x 76 in. (307.1 x 157.5 x 193 cm)		125.7 x 64 x 80 in. (319.4 x 162.5 x 203.2 cm)
Wheelbase	83 in. (211.5 cm)		
Ground Clearance	11 in. (28 cm)	11 in. (28 cm)	13 in. (33 cm)
Cargo Box Dimensions	38 x 54.5 x 12 in. (96.5 x 138.4 x 30.5 cm)		
Cargo Box Capacity	1,000 lb (454 kg)		
Power Tilt Bed	N/A		
Tailgate Load Capacity	250 lb (113.4 kg)		
Storage Capacity	Total: 6.5 gal (24.5 L) Waterproof and removable box under passenger seat: 5.6 gal (21 L) Armrests and cup holders: 0.9 gal (3.5 L)		
Towing Capacity	2,500 lb (1,134 kg)		
Payload Capacity	1,500 lb (680 kg)		
Fuel Capacity	10.6 gal (40 L)		
Person Capacity	3		

FEATURES

Gauge	7.6 in. wide digital display with keypad: speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, ECO™/ECO™ Off/Work modes, seat belt and 4 x 4 indicator, front and rear diff. lock indicators, diagnostics, clock, battery voltage, engine temperature
Battery	12 V (30 amp/h)
Magneto	650 W
Instrumentation	Lighter-type DC outlet in console (20 A)
Lighting	140 W lighting output from four 35-W reflectors ensuring a wide visibility and Premium LED tail lights
Winch	4,500 lb (2,041 kg) winch with roller fairlead
Seat	VERSA-PRO bench seat with passenger seats flipping up, underside hooks, reinforced seat skin and contoured bench to improve entrance/exit of the cab
Steering Wheel	Adjustable tilt steering
Protection	Integrated front steel bumper, HMWPE full skid plate
Hitch Type	2 in. hitch receiver