

can-am

MAVERICK TRAIL DPS 700 / 1000

2022

HIGHLIGHTS

AGILE	<ul style="list-style-type: none"> Sturdy engine and transmission Easy handling and capabilities Front and rear suspension designed for trail riding
ADVENTUROUS	<ul style="list-style-type: none"> Meaningful and versatile functionality Enhanced comfort with Ergo-Lok cockpit Build the Maverick Trail that fits your needs
CONFIDENT	<ul style="list-style-type: none"> Can-Am design and proven fit and finish Enhanced protection More adventure and less maintenance
PLATFORM FEATURES	<ul style="list-style-type: none"> 50 in. wide 90.6 in. wheelbase 10 in. of ground clearance Up to 10.5 in. of suspension travel 4.5 in. digital display SPORT/ECO™ modes Half door (Only for 1000)
SPECIFIC TO DPS PACKAGE	<ul style="list-style-type: none"> Dynamic Power Steering (DPS™) Visco-Lok† QE front differential 12 in. aluminum wheels Ergoprint seats with color accents



- Triple Black / 700 / 1000
- Octane Blue / 1000
- Mossy Oak® Break-Up Country Camo / 1000

ENGINES	700	1000
Type	52 hp, Rotax 650 cc single cylinder, liquid-cooled	75 hp, Rotax 976 cc, V-twin, liquid-cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)	
Transmission	PDrive primary CVT with engine braking and Electronic Drive Belt Protection L/H/N/R/P	Quick Response System (QRS) CVT with high-airflow ventilation and Electronic Drive Belt Protection Extra-L/H/N/R/P
Drive Train	Selectable 2WD/4WD with Visco-Lok QE auto-locking front differential	
Driving Assistance	Electronic Hill Descent Control SPORT/ECO™ modes	
Power Steering	Dynamic Power Steering (DPS)	

SUSPENSIONS

Front Suspension	Double A-arm with sway bar/10 in. (25.4 cm) travel
Front Shocks	Twin tube gas-charged shocks
Rear Suspension	TTA with sway bar/10.5 in. (26.7 cm) travel
Rear Shocks	Twin tube gas-charged shocks

TIRES & WHEELS

Front Tires	Carlisle ACT 26 x 8 x 12 in.
Rear Tires	Carlisle ACT 26 x 9 x 12 in.
Wheels	12 in. cast-aluminum

BRAKES

Front	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers

DIMENSIONS & CAPACITIES

	700	1000
Estimated Dry Weight	1,271 lb (576.5 kg)	1,364 lb (618.7 kg)
Chassis/Cage	Profiled cage, ROPS approved	
L x W x H	118 x 50 x 69 in. (300.5 x 127 x 175.3 cm)	
Wheelbase	90.6 in. (230.1 cm)	
Ground Clearance	10 in. (25.4 cm)	
Cargo Box Capacity	300 lb (136 kg)	
Towing Capacity	1,500 lb (680 kg)	
Storage Capacity	Total: 5.3 gal (20.2 L) Glove box: 4.1 gal (15.6 L) Driver storage: 0.4 gal (1.5 L) Center console and cup holders: 0.8 gal (3.1 L)	
Fuel Capacity	10 gal (38 L)	

FEATURES

Gauge	4.5 in. (11.4 cm) wide digital display: Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO™ mode, seat belt and 4 x 4 indicator, front and rear diff. lock indicators, diagnostics, clock, battery voltage, engine temperature	
Instrumentation	Lighter-type DC outlet in console (20 A)	
Magneto	650 W	
Lighting	Two 55 W reflectors and LED tail lights	
Winch	N/A	
Steering Wheel	Adjustable tilt steering	
Protection	Integrated front steel bumper, Full skid plate	Integrated front steel bumper, Half doors, Full skid plate
Hitch Type	2 in. hitch receiver	

WARRANTY & EXTENDED SERVICE

Factory Warranty	6-month BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 30 months