2026 FREERIDE[®]

Extreme capacity deep snow sled built to live large, live free and go big. The Freeride™ is stable and predictable at higher speed in variable snow conditions, including bigger bumps.

// WHAT'S NEW

- REV® Gen5 Lightweight platform
- Improved Pilot™ DS 4 skis
- Super-short tunnel and radiator (for 154 in.)

// PACKAGE HIGHLIGHTS

- Premium LED headlights
- tMotion™ XT® rear suspension with rigid rear arm
- · Reinforced rails
- E-TEC® SHOT™ starter standard
- Compact deep snow seat
- 10.25 in. touchscreen display with BRP Connect and built-in GPS
- RAS™ 3 front suspension with 930 mm (36 in.) ski stance



ROTAX® ENGINE	850 E-TEC® TURBO R	850 E-TEC®	
Engine details	Liquid-cooled, two-stroke, turbocharged, eRAVE™	Liquid-cooled, two-stroke eRAVE™	
Cylinders – Displacement	2 - 849 cc		
Bore – Stroke	82 x 80.4 mm		
Fuel System	E-TEC® direct injection with additional booster injectors		
Fuel type – Octane	Premium unleaded - 95		
Fuel tank (L)	36		
Oil tank capacity (L)	3.4		
POWERTRAIN			
Drive clutch	pDrive™ with clickers		
Driven clutch	QRS Vent Plus		
Drive sprocket pitch	73 mm (146 in.)		
	89 mm (154 in.)		
DRY WEIGHT			
Dry weight	211 kg (146 in.)	203 kg (146 in.)	
	209 kg (154 in.)	201 kg (154 in.)	
DIMENSIONS			
Vehicle overall length	3,058 mm (146 in.)		
	3,188 mm (154 in.)		
Vehicle overall width	1,073 mm (adjustable)		
Vehicle overall height	1,395 mm		
Ski stance	930 mm (adjustable)		
Available tracks (in.)	PowderMax ¹ :		
(Length x width x profile)	146 x 15 x 2.5		
	PowderMax [†] X-Light:		
	154 X 15 X 3.0		

COLOR		
Scandi Blue		
SUSPENSION		
Front suspension	RAS 3	
Front shock	KYB PRO 40 EA-3	
Front suspension travel	215 mm	
Rear suspension	tMotion XT with rigid rear arm	
Center shock	KYB PRO 40 EA-3	
Rear shock	KYB PRO 40 EA-3	
Rear suspension travel	264 mm	
FEATURES		
Platform	REV® Gen5	
Headlights	Premium LED	
Skis	Pilot DS 4	
Seating	Deep snow compact	
Handlebar	Tapered with J-hooks / Grab handle	
Riser block height	120 mm	
Starter	E-TEC SHOT Starter	
Reverse	RER™	
Brake system	Brembo with adjustable lever	
Heated throttle lever/grips	Standard	
Gauge type	10.25 in. touchscreen display (std on 850 Turbo R) 4.5 in. digital display	
Windshield	No	
Runner (in.) – Carbide (in.)	3/8 square - 4	
Bumpers (front/rear)	Standard / Standard	



